

Plumma's Type N Clear RLA Polymers Pty Ltd

Version No: 2.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: **29/05/2023**Print Date: **30/05/2023**S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

| Product Identifier | |
|-------------------------------|---------------------------------------|
| Product name | Plumma's Type N Clear |
| Chemical Name | Not Applicable |
| Synonyms | Not Available |
| Proper shipping name | ADHESIVES containing flammable liquid |
| Chemical formula | Not Applicable |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Type N Solvent cement for non pressure joints in PVC-U pipes and fittings. |
|--------------------------|--|
| Relevant identified uses | Use according to manufacturer's directions. |

Details of the manufacturer or supplier of the safety data sheet

| Registered company name | RLA Polymers Pty Ltd |
|-------------------------|---|
| Address | 215 Colchester Road, Kilsyth VIC 3137 Australia |
| Telephone | +61 3 9728 1644, 1800 242 931 |
| Fax | +61 3 9728 6009 |
| Website | www.rlapolymers.com.au |
| Email | sales@rlapolymers.com.au |

Emergency telephone number

| Association / Organisation | RLA Polymers Pty Ltd | CHEMWATCH EMERGENCY RESPONSE (24/7) |
|-----------------------------------|----------------------|-------------------------------------|
| Emergency telephone numbers | +61 3 9728 1644 | +61 1800 951 288 |
| Other emergency telephone numbers | 1800 242 931 | +61 3 9573 3188 |

Once connected and if the message is not in your preferred language then please dial ${\bf 01}$

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

| Poisons Schedule | S5 |
|-------------------------------|---|
| Classification ^[1] | Flammable Liquids Category 2, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3 |
| Legend: | 1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

Label elements

Hazard pictogram(s)





Signal word Dar

Hazard statement(s)

H225 Highly flammable liquid and vapour.

Version No: 2.1 Page 2 of 10 Issue Date: 29/05/2023 Print Date: 30/05/2023

Plumma's Type N Clear

| H319 | Causes serious eye irritation. |
|------|------------------------------------|
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |

Precautionary statement(s) Prevention

| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. | |
|------|--|--|
| P271 | Use only outdoors or in a well-ventilated area. | |
| P240 | Ground and bond container and receiving equipment. | |
| P241 | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. | |

Precautionary statement(s) Response

| P370+P378 | In case of fire: Use alcohol resistant foam or normal protein foam to extinguish. | |
|----------------|--|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |
| P312 | Call a POISON CENTER/doctor/physician/first aider/if you feel unwell. | |
| P337+P313 | If eye irritation persists: Get medical advice/attention. | |

Precautionary statement(s) Storage

| P403+P235 | Store in a well-ventilated place. Keep cool. |
|-----------|--|
| P405 | Store locked up. |

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|--|-----------|---------------------|
| 78-93-3 | 30-70 | methyl ethyl ketone |
| 108-94-1 | 5-10 | cyclohexanone |
| Legend: 1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L: * EU IOEL Vs available | | |

SECTION 4 First aid measures

Description of first aid measures

| | · · | |
|--------------|---|--|
| Eye Contact | If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. | |
| Skin Contact | If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor. | |
| Inhalation | If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. | |
| Ingestion | For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay. | |

Indication of any immediate medical attention and special treatment needed

for simple ketones:

BASIC TREATMENT

[▶] Establish a patent airway with suction where necessary.

Version No: 2.1 Page 3 of 10 Issue Date: 29/05/2023

Plumma's Type N Clear

Print Date: 30/05/2023

- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5mL/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Consider intubation at first sign of upper airway obstruction resulting from oedema
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and

- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- Consult a toxicologist as necessary

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide

Special hazards arising from the substrate or mixture

Fire Incompatibility ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

| Fire Fighting Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water course. | |
|---|--|
| Fire/Explosion Hazard | Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat, flame and/or oxidisers. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. Combustion products include: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. |
| HAZCHEM | •3YE |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Minor Spills | Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. |
|--------------|--|
| Major Spills | Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Version No: 2.1 Issue Date: 29/05/2023 Page 4 of 10

Plumma's Type N Clear

Print Date: 30/05/2023

Containers, even those that have been emptied, may contain explosive vapours.

Do NOT cut, drill, grind, weld or perform similar operations on or near containers.

Contains low boiling substance:

Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.

- Check for bulging containers
- Vent periodically Safe handling
 - Always release caps or seals slowly to ensure slow dissipation of vapours
 - DO NOT allow clothing wet with material to stay in contact with skin
 - Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs
 - Use in a well-ventilated area.
 - Prevent concentration in hollows and sumps.

Other information

- ▶ Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources
- DO NOT store in pits, depression, basement or areas where vapours may be trapped.
- Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- - For low viscosity materials (i): Drums and jerry cans must be of the non-removable head type. (ii): Where a can is to be used as an inner package, the can must have a screwed enclosure.
 - For materials with a viscosity of at least 2680 cSt. (23 deg. C)
 - For manufactured product having a viscosity of at least 250 cSt.
- Storage incompatibility
- Avoid strong bases.
- Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|------------------------------|---------------------|---------------------------|---------------------|---------------------|---------------|---------------|
| Australia Exposure Standards | methyl ethyl ketone | Methyl ethyl ketone (MEK) | 150 ppm / 445 mg/m3 | 890 mg/m3 / 300 ppm | Not Available | Not Available |
| Australia Exposure Standards | cyclohexanone | Cyclohexanone | 25 ppm / 100 mg/m3 | Not Available | Not Available | Not Available |

Emergency Limits

| Ingredient | TEEL-1 | TEEL-2 | TEEL-3 |
|---------------------|---------------|---------------|---------------|
| methyl ethyl ketone | Not Available | Not Available | Not Available |
| cyclohexanone | 60 ppm | 830 ppm | 5000* ppm |

| Ingredient | Original IDLH | Revised IDLH |
|---------------------|---------------|---------------|
| methyl ethyl ketone | 3,000 ppm | Not Available |
| cyclohexanone | 700 ppm | Not Available |

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Individual protection measures, such as personal protective equipment









Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

▶ Wear chemical protective gloves, e.g. PVC.

▶ Wear safety footwear or safety gumboots, e.g. Rubber

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care.

Hands/feet protection

Version No: 2.1 Page 5 of 10 Issue Date: 29/05/2023 Print Date: 30/05/2023

Plumma's Type N Clear

| Body protection | See Other protection below |
|------------------|--|
| Other protection | Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. |

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 5 x ES | A-AUS / Class 1 | - | A-PAPR-AUS / Class 1 |
| up to 25 x ES | Air-line* | A-2 | A-PAPR-2 |
| up to 50 x ES | - | A-3 | - |
| 50+ x ES | - | Air-line** | - |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| Appearance | Clear highly flammable liquid with characteristic MEK like odour; | Clear highly flammable liquid with characteristic MEK like odour; does not mix with water. | | |
|--|---|--|----------------|--|
| | | | | |
| Physical state | Liquid | Relative density (Water = 1) | 0.88-0.9 | |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available | |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | 515 | |
| pH (as supplied) | Not Applicable | Decomposition temperature (°C) | Not Available | |
| Melting point / freezing point (°C) | -86 | Viscosity (cSt) | ~600 | |
| Initial boiling point and boiling range (°C) | 79-81 | Molecular weight (g/mol) | Not Applicable | |
| Flash point (°C) | -16 | Taste | Not Available | |
| Evaporation rate | Not Available | Explosive properties | Not Available | |
| Flammability | HIGHLY FLAMMABLE. | Oxidising properties | Not Available | |
| Upper Explosive Limit (%) | 10 | Surface Tension (dyn/cm or mN/m) | Not Available | |
| Lower Explosive Limit (%) | 1.8 | Volatile Component (%vol) | >75 | |
| Vapour pressure (kPa) | 9.5 | Gas group | Not Available | |
| Solubility in water | Immiscible | pH as a solution (1%) | Not Applicable | |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available | |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|------------------------------------|--|
| Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

Plumma's Type N Clear

Issue Date: **29/05/2023**Print Date: **30/05/2023**

SECTION 11 Toxicological information

| Information | on | toxicological | effects |
|-------------|----|---------------|---------|
|-------------|----|---------------|---------|

| Inhaled | | · · · | | | |
|-----------------------|--|--|--|--|--|
| Ingestion | Accidental ingestion of the material may be damaging to t | he health of the individual. | | | |
| Skin Contact | Open cuts, abraded or irritated skin should not be expose Entry into the blood-stream, through, for example, cuts, at | kin contact with the material may damage the health of the individual; systemic effects may result following absorption. pen cuts, abraded or irritated skin should not be exposed to this material intry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin ior to the use of the material and ensure that any external damage is suitably protected. | | | |
| Eye | The vapour when concentrated has pronounced eye irritate | This material can cause eye irritation and damage in some persons. The vapour when concentrated has pronounced eye irritation effects and this gives some warning of high vapour concentrations. If eye irritation occurs seek to reduce exposure with available control measures, or evacuate area. | | | |
| Chronic | Prolonged or repeated skin contact may cause drying with There has been some concern that this material can caus Substance accumulation, in the human body, may occur a Long term cyclohexanone exposure may cause liver and I Animal testing shows that methyl ethyl ketone may have s also be developmental effects and an increase in birth def | irways disease, involving difficulty breathing and related whole-body problems. In cracking, irritation and possible dermatitis following. The cancer or mutations but there is not enough data to make an assessment. The cancer or mutations but there is not enough data to make an assessment. The cancer or mutations but there is not enough data to make an assessment. The cancer following repeated or long-term occupational exposur kidney changes. Clouding of the eye lens and cataract development may occur. Slight effects on the nervous system, liver, kidney and respiratory system; there may fects. However, there is limited information available on the long-term effects of mether it causes developmental or reproductive toxicity or cancer. It is generally | | | |
| | ** | bination with other solvents, and the toxic effects of the mixture may be greater thar ethyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral | | | |
| Discount Time M Class | with either solvent alone. Combinations of n-hexane or me | bination with other solvents, and the toxic effects of the mixture may be greater thar ethyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral | | | |
| Plumma's Type N Clear | with either solvent alone. Combinations of n-hexane or me neuropathy, a progressive disorder of the nerves of the ex | bination with other solvents, and the toxic effects of the mixture may be greater than ethyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral stremities. | | | |
| Plumma's Type N Clear | with either solvent alone. Combinations of n-hexane or me neuropathy, a progressive disorder of the nerves of the ex | bination with other solvents, and the toxic effects of the mixture may be greater than ethyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral stremities. IRRITATION | | | |
| Plumma's Type N Clear | with either solvent alone. Combinations of n-hexane or me neuropathy, a progressive disorder of the nerves of the ex TOXICITY Not Available | bination with other solvents, and the toxic effects of the mixture may be greater than ethyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral stremities. IRRITATION Not Available | | | |
| Plumma's Type N Clear | with either solvent alone. Combinations of n-hexane or me neuropathy, a progressive disorder of the nerves of the ex TOXICITY Not Available TOXICITY | bination with other solvents, and the toxic effects of the mixture may be greater than ethyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral tremities. IRRITATION Not Available IRRITATION | | | |
| | with either solvent alone. Combinations of n-hexane or me neuropathy, a progressive disorder of the nerves of the ex TOXICITY Not Available TOXICITY Dermal (rabbit) LD50: 6480 mg/kg ^[2] | bination with other solvents, and the toxic effects of the mixture may be greater than ethyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral tremities. IRRITATION Not Available IRRITATION Eye (human): 350 ppm -irritant | | | |
| | with either solvent alone. Combinations of n-hexane or me neuropathy, a progressive disorder of the nerves of the example. TOXICITY Not Available TOXICITY Dermal (rabbit) LD50: 6480 mg/kg ^[2] Inhalation(Mouse) LC50; 32 mg/L4h ^[2] | bination with other solvents, and the toxic effects of the mixture may be greater than ethyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral stremities. IRRITATION Not Available IRRITATION Eye (human): 350 ppm -irritant Eye (rabbit): 80 mg - irritant | | | |
| | with either solvent alone. Combinations of n-hexane or me neuropathy, a progressive disorder of the nerves of the example. TOXICITY Not Available TOXICITY Dermal (rabbit) LD50: 6480 mg/kg ^[2] Inhalation(Mouse) LC50; 32 mg/L4h ^[2] | bination with other solvents, and the toxic effects of the mixture may be greater than ethyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral tremities. IRRITATION Not Available IRRITATION Eye (human): 350 ppm -irritant Eye (rabbit): 80 mg - irritant Skin (rabbit): 402 mg/24 hr - mild | | | |
| | with either solvent alone. Combinations of n-hexane or me neuropathy, a progressive disorder of the nerves of the example of the nerves of the nerves of the example of the nerves of the nerv | bination with other solvents, and the toxic effects of the mixture may be greater than eithyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral tremities. IRRITATION Not Available IRRITATION Eye (human): 350 ppm -irritant Eye (rabbit): 80 mg - irritant Skin (rabbit): 402 mg/24 hr - mild Skin (rabbit): 13.78mg/24 hr open - mild | | | |
| | with either solvent alone. Combinations of n-hexane or me neuropathy, a progressive disorder of the nerves of the ex TOXICITY Not Available TOXICITY Dermal (rabbit) LD50: 6480 mg/kg ^[2] Inhalation(Mouse) LC50; 32 mg/L4h ^[2] Oral (Rat) LD50: 2054 mg/kg ^[1] TOXICITY | bination with other solvents, and the toxic effects of the mixture may be greater than ethyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral tremities. IRRITATION Not Available IRRITATION Eye (human): 350 ppm -irritant Eye (rabbit): 80 mg - irritant Skin (rabbit): 402 mg/24 hr - mild Skin (rabbit): 13.78mg/24 hr open - mild IRRITATION IRRITATION | | | |
| methyl ethyl ketone | with either solvent alone. Combinations of n-hexane or me neuropathy, a progressive disorder of the nerves of the example of the nerves of the nerv | bination with other solvents, and the toxic effects of the mixture may be greater than eithyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral tremities. IRRITATION Not Available IRRITATION Eye (human): 350 ppm -irritant Eye (rabbit): 80 mg - irritant Skin (rabbit): 402 mg/24 hr - mild Skin (rabbit): 13.78mg/24 hr open - mild IRRITATION Eye (human): 75 ppm | | | |

METHYL ETHYL KETONE

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.

Methyl ethyl ketone is considered to have a low order of toxicity; however, methyl ethyl ketone is often used in combination with other solvents and the mixture may have greater toxicity than either solvent alone. Combinations of n-hexane with methyl ethyl ketone, and also methyl n-butyl ketone with methyl ethyl ketone may result in an increased in peripheral neuropathy, a progressive disorder of the nerves of the extremities. Combinations with chloroform also show an increase in toxicity.

CYCLOHEXANONE

Cyclohexanone irritates the eye and the skin. Signs of CNS depression and weight loss have been noted at higher doses. Other features of toxicity include mottling of the lungs and degenerative changes in the liver and kidney. It is not considered to cause cancers, but it may reversibly reduce fertility.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may

produce conjunctivitis.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.

METHYL ETHYL KETONE & CYCLOHEXANONE

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

| Acute Toxicity | × | Carcinogenicity | × |
|-----------------------------------|---|--------------------------|---|
| Skin Irritation/Corrosion | × | Reproductivity | × |
| Serious Eye Damage/Irritation | ✓ | STOT - Single Exposure | ✓ |
| Respiratory or Skin sensitisation | × | STOT - Repeated Exposure | × |
| Mutagenicity | × | Aspiration Hazard | × |

Legend: X – Data either not available or does not fill the criteria for classification

Version No: 2.1 Page 7 of 10 Issue Date: 29/05/2023

Plumma's Type N Clear

Print Date: 30/05/2023

Data available to make classification

SECTION 12 Ecological information

Toxicity

| | Endpoint | Test Duration (hr) | Species | Value | Source |
|-----------------------|----------------------------------|--------------------------------------|--|----------------------------------|------------------|
| Plumma's Type N Clear | Not Available | Not Available | Not Available | Not Available | Not Available |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| methyl ethyl ketone | NOEC(ECx) | 48h | Crustacea | 68mg/l | 2 |
| | EC50 | 96h | Algae or other aquatic plants | >500mg/l | 4 |
| | EC50 | 72h | Algae or other aquatic plants | 1220mg/l | 2 |
| | LC50 | 96h | Fish | >324mg/L | 4 |
| | EC50 | 48h | Crustacea | 308mg/l | 2 |
| | Endpoint | Test Duration (hr) | Species | Value | Sourc |
| | LC50 | 96h | Fish | 481-578mg/l | 4 |
| cyclohexanone | EC50 | 72h | Algae or other aquatic plants | 17.7-85.6mg/l | 4 |
| | EC50 | 48h | Crustacea | >100mg/l | 2 |
| - | EC10(ECx) | 72h | Algae or other aquatic plants | 0.4-7.93mg/l | 4 |
| Legend: | Extracted from Ecotox databas | 1. IUCLID Toxicity Data 2. Europe E0 | Algae or other aquatic plants CHA Registered Substances - Ecotoxicological Info Aquatic Hazard Assessment Data 6. NITE (Japan | ormation - Aquatic Toxicity 4. U | JS I |

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|---------------------|---------------------------|------------------------------|
| methyl ethyl ketone | LOW (Half-life = 14 days) | LOW (Half-life = 26.75 days) |
| cyclohexanone | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|---------------------|---------------------|
| methyl ethyl ketone | LOW (LogKOW = 0.29) |
| cyclohexanone | LOW (BCF = 2.45) |

Mobility in soil

| , | |
|---------------------|----------------------|
| Ingredient | Mobility |
| methyl ethyl ketone | MEDIUM (KOC = 3.827) |
| cyclohexanone | LOW (KOC = 15.15) |

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

▶ DO NOT allow wash water from cleaning or process equipment to enter drains.

- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ► Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers.

SECTION 14 Transport information

Labels Required

Version No: 2.1 Page 8 of 10 Issue Date: 29/05/2023 Print Date: 30/05/2023

Plumma's Type N Clear



Land transport (ADG)

HAZCHEM

•3YE

| UN number or ID number | 1133 | |
|------------------------------|---|--|
| UN proper shipping name | ADHESIVES containing flammable liquid | |
| Transport hazard class(es) | Class 3 Subsidiary risk Not Applicable | |
| Packing group | | |
| Environmental hazard | Not Applicable | |
| Special precautions for user | Special provisions Not Applicable Limited quantity 5 L | |

Air transport (ICAO-IATA / DGR)

| UN number | 1133 | | |
|------------------------------|---|----------------|------|
| | 1133 | | |
| UN proper shipping name | Adhesives containing fla | mmable liquid | |
| | ICAO/IATA Class | 3 | |
| Transport hazard class(es) | ICAO / IATA Subrisk | Not Applicable | |
| | ERG Code | 3L | |
| Packing group | Ш | | |
| Environmental hazard | Not Applicable | | |
| | Special provisions | | А3 |
| | Cargo Only Packing Instructions | | 364 |
| | Cargo Only Maximum | Qty / Pack | 60 L |
| Special precautions for user | Passenger and Cargo Packing Instructions | | 353 |
| | Passenger and Cargo Maximum Qty / Pack | | 5 L |
| | Passenger and Cargo Limited Quantity Packing Instructions | | Y341 |
| | Passenger and Cargo Limited Maximum Qty / Pack | | 1 L |

Sea transport (IMDG-Code / GGVSee)

| UN number | 1133 | |
|------------------------------|---------------------------------------|------------------------------|
| UN proper shipping name | ADHESIVES containing flammable liquid | |
| Transport hazard class(es) | IMDG Class 3 IMDG Subrisk Not | Applicable |
| Packing group | | |
| Environmental hazard | Not Applicable | |
| Special precautions for user | Special provisions | F-E, S-D Not Applicable 5 L |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|---------------------|---------------|
| methyl ethyl ketone | Not Available |
| cyclohexanone | Not Available |

Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|---------------------|---------------|
| methyl ethyl ketone | Not Available |
| cyclohexanone | Not Available |

Version No: 2.1 Page 9 of 10 Issue Date: 29/05/2023 Print Date: 30/05/2023

Plumma's Type N Clear

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

methyl ethyl ketone is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -

Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

cyclohexanone is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

National Inventory Status

| National Inventory | Status |
|--|--|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | No (methyl ethyl ketone; cyclohexanone) |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | Yes |
| Japan - ENCS | Yes |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | Yes |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | Yes |
| Vietnam - NCI | Yes |
| Russia - FBEPH | Yes |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

| Revision Date | 29/05/2023 |
|---------------|------------|
| Initial Date | 18/05/2023 |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

Version No: 2.1 Page 10 of 10 Issue Date: 29/05/2023 Print Date: 30/05/2023

Plumma's Type N Clear

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances